

## GRIPPER FINER



### SPECIFICATIONS

**Specific weight at 20°C:** 1.05 ± 0.05 kg/lt  
**Volume of solid content:** 49% ± 1%  
**Concrete adherence:** > 1 breakage A/B MPa - UNI EN 1542  
**UV resistance:** high (ASTM G53)  
**Water vapour transmission:** 1\*104 μ - UNI EN 7783-2012  
**Resistance to artificial weathering after 2000 h:** no swelling, cracking or scaling – UNI EN 1062 - 11  
**Volatile organic matter content:** < 2 g/lt  
**Theoretical consumption:** 0.100–0.120 kg/m2  
**Drying time at 25°C and 65% RH:** 3-4 hours

<b>Description</b>	Breathable resin-based adhesion promoter with acrylic binders modified with organosilanes in an aqueous solution. Contains nanotechnological products to improve the structure and general resistance. Ideal for integrating in heat insulating skim coat cycles using nanotechnological products and others. This product is to be used as a primer for Savenergy plaster.
<b>Main uses</b>	Impregnation of powdery or damaged internal surfaces. Impregnation and primer coat for external surfaces exposed to rising damp or the weather.
<b>Application methods</b>	Plaster surfaces or masonry must be in dry and in good condition, without friable parts. Before applying the product, clean the surface by pressure washing or wet or dry sandblasting. The product must be previously homogenized in the can with a mechanical agitator. To apply with a roller or a brush, dilute the product with clean water in a ratio of 1 to 4. An airless spray system can be used if the product is diluted with water in a ratio of 1 to 8. Greater dilutions are possible depending on the surface quality and conditions.
<b>Warnings</b>	Application temperature: from + 5°C to + 35°C on the surface Operating temperature: from +5 to +35°C on the surface
<b>Storage stability</b>	The product is guaranteed for one year if it is stored in its original packaging and in a dry, protected place. It is advisable to store the product at a temperature between +5°C and +35°C.
<b>Packages</b>	20 lt pails Standard colour: semi-transparent. Safety: consult the relative safety data sheet for information.

All information contained in this technical sheet is based on the best practical experience and laboratory testing. The customer is responsible for verifying that the product is suitable for the intended use. The manufacturer declines all responsibility for results deriving from incorrect applications. This sheet replaces and voids all previous sheets. The data may vary at any time. The manufacturer is not obligated to give prior notice.

