

MUFFASTEM - TRANSP. INTERNAL



SPECIFICATIONS

Specific weight: 1.0 kg/lit

Drying time at 20°C: 24 h

Solvent: water

Consumption: 100-150 g/m²

Description	MUFFASTEM is a transparent or white liquid product that deeply penetrates surfaces. It is suitable for destroying any fungal spores present and protecting against the possible infiltration of new spores. The product is based on water and sodium hypochlorite. When properly diluted, it provides permanent defence. Contains surfactants for adequate distribution, even deep down.
Main uses	MUFFASTEM should be applied on gauged or cement mortar structures affected by algae and mould. It can also be used to protect paint or coatings.
Application methods	Painted dry surfaces made of cement mortar or lime. Apply by brushing or spraying on the surface to be cleaned and wait at least 5 hours. Then brush the surface with a hard-bristled broomcorn scrubber to remove dead spores. Perform a second similar treatment at the most affected points. After the surface has dried, apply any chosen products from the anti-algae or anti-mould series following the instructions.
Warnings	The product should be applied indoors while keeping the premises ventilated. The product may discolour the underlying surface or those with which it comes into contact.
Packages	5 lt canisters

All information contained in this technical sheet is based on the best practical experience and laboratory testing. The customer is responsible for verifying that the product is suitable for the intended use. The manufacturer declines all responsibility for results deriving from incorrect applications. This sheet replaces and voids all previous sheets. The data may vary at any time. The manufacturer is not obligated to give prior notice.

